



**THOMSON**  
DELPHION

RESEARCH
PRODUCTS
INSIDE DELPHION

My Account | Products
Search: Quick/Number Boolean Advanced

## The Delphion Integrated View

Get Now: ☒ PDF | [More choices...](#)

Tools: Add to Work File: [Create new Wor](#)

View: [INPADOC](#) | Jump to:

Go to: [Derwent...](#)

[Email](#)

Title: **JP4206366A2: FLAT BATTERY**

Country: **JP** Japan

Kind: **A**

Inventor: **NAKAI KENJI;**  
**HIGASHIMOTO KOJI;**  
**HIRONAKA KENSUKE;**  
**HAYAKAWA TAKUMI;**  
**KOMAKI AKIO;**  
**NAKANAGA TAKEFUMI;**  
**TANIGUCHI MASATOSHI;**

Assignee: **SHIN KOBE ELECTRIC MACH CO LTD.**  
**OTSUKA CHEM CO LTD.**  
[News, Profiles, Stocks and More about this company](#)

Published / Filed: **1992-07-28 / 1990-11-30**

Application Number: **JP1990000333743**

IPC Code: **H01M 10/40; H01M 4/02**

Priority Number: **1990-11-30 JP1990000333743**


Abstract:
   
 ... PURPOSE: To prevent the aggravation of the battery performance by laminating a flat positive electrode active material and a negative electrode active material through a solid electrolyte, covering these generating elements with a collector, divisionally forming the positive electrode active material on the collector, and sealing the peripheral part by a sealing material.
   
 ... CONSTITUTION: On a stainless foil used as both a battery sheath and a collector 1, an aqueous solution of vanadium pentoxide which is a positive electrode material 2 is finely applied by means of screen printing, dried and heated. For example, a 1,2-dimethoxyethane(DME) solution of a polyphosphadine derivative in which 1mol/l of lithium perchlorate is dissolved is applied thereon by means of screen printing, and the DME is evaporated to form a solid electrolyte 3. A metal lithium foil is stuck thereon as a negative electrode active material 4, and further covered with the stainless foil of a collector 1', and the peripheral part is thermally fused by a sealing material 5 such as a modified polyethylene resin and sealed. Thus, the aggravation of the battery performance can be prevented.
   
 ... COPYRIGHT: (C)1992,JPO&Japio.

Family: **None**

Other Abstract: **None**



Info:



[Nominate](#)

[this for the Gallery...](#)

© 1997-2003 Thomson Delphion    [Research Subscriptions](#) | [Privacy Policy](#) | [Terms & Conditions](#) | [Site Map](#) | [Contact](#)



(19)

(11) Publication number: **04**

Generated Document.

**PATENT ABSTRACTS OF JAPAN**(21) Application number: **02333743**(51) Intl. Cl.: **H01M 10/40 H01M 4/02**(22) Application date: **30.11.90**

|   |  |
|---|--|
| <p>(30) Priority:</p> <p>(43) Date of application publication: <b>28.07.92</b></p> <p>(84) Designated contracting states:</p> | <p>(71) Applicant: <b>SHIN KOBE ELECTRIC LTD.<br/>OTSUKA CHEM CO LT</b></p> <p>(72) Inventor: <b>NAKAI KENJI<br/>HIGASHIMOTO KOJI<br/>HIRONAKA KENSUKE<br/>HAYAKAWA TAKUMI<br/>KOMAKI AKIO<br/>NAKANAGA TAKEFUM<br/>TANIGUCHI MASATOSH</b></p> <p>(74) Representative:</p> |
|---|--|

**(54) FLAT BATTERY****(57) Abstract:**

**PURPOSE:** To prevent the aggravation of the battery performance by laminating a flat positive electrode active material and a negative electrode active material through a solid electrolyte, covering these generating elements with a collector, divisionally forming the positive electrode active material on the collector, and sealing the peripheral part by a sealing material.

**CONSTITUTION:** On a stainless foil used as both a battery sheath and a collector 1, an aqueous solution of vanadium pentoxide which is a positive electrode material 2 is finely applied by means of screen printing, dried and heated. For example, a 1,2-dimethoxyethane(DME) solution of a

polyphosphadine derivative in which 1mol/l of lithium perchlorate is dissolved is applied thereon by means of screen printing, and the DME is evaporated to form a solid electrolyte 3. A metal lithium foil is stuck thereon as a negative electrode active material 4, and further covered with the stainless foil of a collector 1', and the peripheral part is thermally fused by a sealing material 5 such as a modified polyethylene resin and sealed. Thus, the aggravation of the battery performance can be prevented.

COPYRIGHT: (C)1992,JPO&Japio

